


GRUPOS ELECTROGENOS MARINOS MARINE GENERATING SETS



En un medio imprevisible como es el mar, en el que el suministro de energía eléctrica es de vital importancia, nuestros grupos electrógenos Solé Diesel satisfacen los más altos requerimientos en lo que refiere a fiabilidad, prestaciones y durabilidad, bajo condiciones severas de funcionamiento.

Nuestra larga experiencia en la fabricación de motores marinos complementada con la más reciente tecnología nos avalan.

CARACTERÍSTICAS GENERALES

Motores de bajo consumo y nivel de emisiones.
Sistema de doble circuito de refrigeración con circuito de líquido refrigerante.
Montaje monoblock con suspensores que amortiguan las vibraciones garantizando un funcionamiento estable y silencioso.
Bancada rígida de alta resistencia.
Alternadores síncronos autoexcitados y sin escobillas.
Modelos trifásicos y monofásicos
Frecuencias disponibles de 50 o 60 Hz.
Regulador electrónico de tensión que garantiza una variación de tensión menor al 2,5% con independencia de la carga y la temperatura ambiental.

EQUIPAMIENTO STANDARD

Refrigeración por intercambiador de calor
Arranque eléctrico de 12V
Alternador de motor de 12V
Cuadro de mandos a distancia
Parada automática por baja presión de aceite o alta temperatura de líquido de refrigeración.

The sea is an unpredictable medium where an energy source is of great importance.
Our generating sets work continuously to satisfy the highest requirements with reliability, durability and best performance under extreme working conditions.

Our long experience building marine engines with the latest innovations in technology support us.

TECHNICAL DATA

Engines with low consumption and low exhaust emission levels .
Double cooling circuit using cooling liquid to avoid corrosion which works at a wide range of temperatures.
Silentblocks to dampen vibrations and guarantee stable and silent work.
Rigid high resistance frame.
Synchronous alternators, self-activated and brushless.
Triphasic and monophasic sets.
Suitable frecuencys of 50 or 60 Hz.
Electronic voltage regulator, that ensures less than a 2,5% variation under load or temperature variations.

STANDARD EQUIPMENT

Cooled by heat exchanger.
12V Starting motor
12V Alternator
Control Panel outside of engine room
Automatic stop under low oil pressure or high cooling liquid temperature.

ALTERNADORES MONOFÁSICOS - SINGLE PHASE ALTERNATORS

R.P.M.	MODEL MODEL MODÈLE	MOTOR ENGINE MOTEUR	VOLTAJE VOLTAGE (VOLT)		POTENCIA DE SALIDA POWER OUTPUT (kVA)		DIMENSIONES DIMENSIONS (mm)			PESO WEIGHT (kg)
			50 Hz.	60 Hz.	50 Hz.	60 Hz.	(A)	(B)	(C)	
1500 (50 Hz) 1800 (60 Hz)	G-6M-15	MINI-26	400/230	480/240	6	7	990	547	465	215
	G-10M-15	MINI-33	400/230	480/240	9	11	1137	596	524	250
	G-15M-15	MINI-44	400/230	480/240	15	17	1195	605	524	370
	G-20M-15	MINI-62	400/230	480/240	20	23	1370	695	577	480
	G-35M-15	MINI-74	400/230	480/240	33	39	1381	725	655	312
3000 (50 Hz)	G-8M-3X	MINI-17	400/230	-	8	-	889	547	482	163
	G-15M-3	MINI-26	400/230	-	15	-	1112	547	482	305
	G-25M-3	MINI-44	400/230	-	25	-	1295	605	524	420

ALTERNADORES TRIFÁSICOS - THREE PHASE ALTERNATORS

R.P.M.	MODEL MODEL MODÈLE	MOTOR ENGINE MOTEUR	VOLTAJE VOLTAGE (VOLT)		POTENCIA DE SALIDA POWER OUTPUT (kVA)		DIMENSIONES DIMENSIONS (mm)			PESO WEIGHT (Kg)
			50 Hz	60 Hz	50 Hz	60 Hz	(A)	(B)	(C)	
1500 (50 Hz) 1800 (60 Hz)	G-6T-15	MINI-26	400/230	480/240	6	7	990	547	465	196
	G-10T-15	MINI-33	400/230	480/240	10	12	1137	596	524	272
	G-15T-15	MINI-44	400/230	480/240	15	17	1115	605	524	320
	G-20T-15	MINI-62	400/230	480/240	20	24	1335	645	577	389
	G-35T-15	MINI-74	400/230	480/240	34	40	1381	725	655	547
	G-51T-15	SM-105	400/230	480/240	50	60	1721	790	655	745
	G-80T-15	SFN-160	400/230	480/240	80	96	1953	921	670	1140
3000 (50 Hz)	G105T-15	SFN-210	400/230	480/240	105	126	1936	921	760	1158
	G-8T-3	MINI-17	400/230	-	8	-	881	547	482	165
	G-15-T3	MINI-26	400/230	-	15	-	1070	547	465	223
	G-25T-3	MINI-44	400/230	-	25	-	1260	605	524	352